RELIANCE
ECO CARPET CUSHION

Saving Our Planet One Square Yard At A Time

www.reliancecarpetcushion.com

100% SYNTHETIC FIBER CUSHION
USED UNDER AUTO CARPETS, SEAT BACKING AND LINERS
REDUCES VIBRATION, NOISE, ABSORBS IMPACT AND INSULATES

SPECIFICATIONS

PRODUCT: AUTO PAD II - ECO CARPET CUSHION
CONTENT: 100% POST-CONSUMER RECYCLED SYNTHETIC FIBERS

DENSITY (ASTM D3776)	7.0 lbs. per cubic foot (approx.)
THICKNESS:	3/8" (approx.)
ROLL WIDTH:	3'
ROLL LENGTH:	150'
ROLL WEIGHT:	87.5 lbs. (approx.)
YARDAGE PER ROLL	50 S.Y.
TEAR STRENGTH (ASTM 2262)	40 lbs.
ELONGATION TESTS	13% avg.
FOOT TRAFFIC (300,000 MIN)	Pass
ACOUSTICAL NRC: (A.S.T.M.C423-77)	.68
INSULATION "R" FACTOR: (A.S.T.M. C518-76)	2.24
ODOR/MILDEW:	None
RADIANT PANEL (ASTM E 648)	Class 1
FLAMMABILITY DOC-FF-1-70 (Pill Test)	Pass
SMOKE DENSITY ASTM E 662	Pass

Manufacturer warrants that its carpet cushion products are free from any defects in workmanship and material for the life of the carpet under which they are originally installed. This warranty applies only when properly installed over flat, smooth, hard surfaces on, or above grade. This warranty specifically excludes stairs and is applicable to the original purchaser of the carpet cushion only.

Should a manufacturing defect exist which affects the quality and performance of this carpet cushion, the manufacturer, as a sole and exclusive remedy, will replace, without charge, the defective cushion F.O.B. manufacturing plant. This warranty is specifically restricted to carpet cushion replacement only. This warranty does not include the cost of removal or installation. No liability will be assumed for any consequential damage, loss or expense.

100% Recyclable – Made in the USA

SHOWROOM: 10635 SANTA MONICA BLVD., LOS ANGELES, CA 90255 • BY APPOINTMENT ONLY • 323.321.2300 • info@reliancecarpetcushion.com